

HC 401 PVC Tape

PRODUCT DATA SHEET



CONSTRUCTION

Substrate: 6-mil PVC Film
Adhesive: Rubber
Liner: None



FEATURES

- Rubber based adhesive
- Bonds well to PVC fittings and pipe
- Performs well in challenging environmental conditions
- Resistant to many chemicals
- Available colors: black, orange, green, blue, white, red, yellow, clear, gray and brown

TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Total Thickness	0.006-in	0.152-mm	PSTC-133
Peel Adhesion to Stainless Steel	20-oz/in	2.2-N/cm	PSTC-101
Tensile Strength	14-lbs/in	25-N/cm	PSTC-131
Elongation	150%	150%	PSTC-131

APPLICATION

Application surface must be clean, dry and free of contaminants.

SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
1-in	108-ft	48	27
1.5-in	108-ft	32	27
2-in	108-ft	24	27
3-in	108-ft	16	27

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 1.12.2010 08:20.