



# LAMART CORPORATION

Flexible Laminate Solutions

## Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

**PRODUCT ID:** 520 L TAPE

**DESCRIPTION:** **PRESSURE SENSITIVE PRODUCTS**  
Products Engineered to your Specifications

**CONSTRUCTION:** Backing: 0.002" Aluminum Foil  
Adhesive: Acrylic  
Interliner: Silicone release liner

**APPLICATION:** HVAC- Joining and sealing laminated fiberglass blankets, ducts, joints and seams for both rigid and flexible constructions.  
Industrial – Moisture / vapor barrier, heat reflective, sealing out dust and dirt in underground cable applications.

**BENEFITS:** Dead soft aluminum foil is highly conformable to both irregular and curved surfaces, offering excellent resistance to dust, dirt and water / vapor transmission.

Aggressive acrylic adhesive offers excellent adhesion and shear characteristics for HVAC applications.

Highly reflective aluminum tape surface, combined with a service temperature range of -40F to 350F (-40C to 177C), allows this tape to be used in a broad range of environments.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Foil:	.002" (50 microns)	ASTM-D-3652
Total thickness w/o liner	0.0033" (84 microns)	ASTM-D-3652
Peel Adhesion:	45 oz./in. (21.3N/25mm)	ASTM-D-1000
Breaking Strength:	17 # / in. (77N/25mm)	ASTM-D-1000
Elongation at Break:	3.5% (3.5%)	ASTM-D-1000
Service Temperature:	-40F to 350F (-40C to 177C)	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

Application Conditions: Apply to clean, dry surface when surface temperature is between 50F and 105F (10C and 40C)

P/N 16171

Rev1 : 10/29/09

*Physical and performance values, characteristics, etc. shown above are obtained from recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.*