LAMART CORPORATION
Flexible Laminate Solutions

Technical Data

www.lamartcorp.com
800-LAMART9
973-772-6262

PRODUCT ID: 245-L-R Tape

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**
Products Engineered to your Specifications

CONSTRUCTION:
Backing: 0.005" Lead Foil
Adhesive: Rubber
Interliner: Polycoated Paper Liner

FEATURES / BENEFITS:
Highly conformable to both irregular and curved surfaces.

Aggressive Rubber PS adhesive is designed to offer excellent quick stick and ultimate adhesion.

Liner allows tape to be die cut into shapes.

SPECIFICATION: Complies with Fed. Spec. HH-T-29A amendment 2

APPLICATION:

MASKING
Electroplating
X-ray plates
Chemical milling

SEALING
Radioactive canisters

SHIELDING
Radiation barrier

PROPERTY	VALUE	TEST METHOD
Thickness w/o liner:	0.006 inch +/- 10%	ASTM-D-3652
Peel Strength:	> 60 oz per inch width	ASTM-D-1000
Breaking Strength:	18 lbs./inch of width	ASTM-D-1000
Elongation at Break:	15%	ASTM-D-1000
Color:	Natural	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 16366 Date: 02/22/08

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.