



# LAMART CORPORATION

Flexible Laminate Solutions

## Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: LSV-600-C-TC-70 PRT

DESCRIPTION: **GRAPHIC ARTS**  
Laminates and Coated Products Engineered for the Graphic Arts Industry

CONSTRUCTION: Nominal 5.5 mil clear static PVC /  
70 lb printable liner (no adhesive)

FEATURES: "Cling" qualities of PVC allow adhesion to most  
clean, smooth surfaces without the use of adhesive.  
PVC is coated with a barrier coat to minimize plasticizer  
migration and improve printability.

APPLICATION: Ultimate removability. Point of purchase displays.  
Temporary signs. Seasonal decorations.

PRINTING METHODS (topcoated): Flexographic  
Letterpress  
Offset  
Screen

CHEMICAL PROPERTIES: Solvent Resistance: Poor  
Water Resistance: Fair  
Humidity Resistance: Fair

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness w/o liner:	0.0055" nominal	ASTM-D-3652
Service Life:	2 years	
Color:	Clear	
Dimensional Stability:	Fair	
Application Temperature:	50 degrees F. minimum	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	
Service Temperature:	- 40 to 150 deg. F.	

P/N 17104

Date 03/03/10

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.*

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics