



# LAMART CORPORATION

Flexible Laminate Solutions

## Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: M-2000-TC-50DK

DESCRIPTION: **GRAPHIC ARTS**  
Laminates and Coated Products Engineered for the Graphic Arts Industry

CONSTRUCTION: Backing: 0.002" Metallized Topcoated Polyester Film  
Adhesive: 0.0009" Acrylic Pressure Sensitive Adhesive  
Interliner: 50 lb. Densified Kraft Release Liner

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Tensile Strength:	20,000 psi minimum	ASTM-D-882
Elongation:	90% minimum	ASTM-D-882
Breaking Strength:	40 lbs per inch minimum	ASTM-D-882
Yield:	5.5 sq. yards per lb	
Peel Strength:	32 oz. / inch minimum	ASTM-D-1000
Release Value:	50gms / inch maximum	LTM-18*

\*Lamart test method, available upon request

Shelf Life: 1 year when stored under conditions of  
70 degrees F. (21 degrees C.) and 50% R.H.

P/N: 185

Rev 1: 07/07/10

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.*

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics