



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT: D/C Syn Rub Pet Tape

DESCRIPTION: **CUSTOM PRESSURE SENSITIVE PRODUCTS**

CONSTRUCTION: 3 Mil C2S RELEASE PET/2.0 MILS RUBBER PSA/1 MIL PET/2.0 MILS RUBBER PSA

ADHESIVE: SPECIALTY RUBBER PSA

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
<u>180° PEEL ADHESION TO GLASS</u> <u>Immediate:</u>	Backside / Faceside 80 ozs. / 75 ozs .	 PSTC 101 Method C Dow method QC101A26 & QC101A27
24 hrs @ RT	85 ozs. / 80 ozs.	
SHEAR ADHESION TO STAINLESS STEEL @ 160°F	>300 min.	PSTC 107 METHOD D Dow Method QC105A04

Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics