



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: 1112-78

DESCRIPTION: 1112 is a general purpose 3 mil acrylic transfer adhesive. The adhesive adheres well to plastic, rubber and foam substrates

CONSTRUCTION: 2.0 mil acrylic transfer adhesive. Available on 60lb., 78Lb., 80lb kraft paper liners. Also available on a 12 Pt board stock.

BENEFITS High tack, good shear, exhibits good adhesion to closed cell sponge rubber, open cell urethane foam and polar substrates.

PROPERTY	VALUE	TEST METHOD
	-	PSTC 101 Method A
2 mil PET Backing 180° Peel Adhesion 20 min @ RT	Stainless Steel 120 ozs./in.	
Ozs./inch 24 Hrs. @ RT Ozs./inch	 125 ozs./in.	

Shear Adhesion 1 X 1 X 1000g 2.2 PSI Hours	Stainless steel >20 hrs	Procedure A
---	--------------------------------	-------------

Rolling Ball Tack Inches	3.0 inch	PSTC 6
-----------------------------	----------	--------

PN 19169

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics