



# DATA SHEET

## ELECTROSHIELD

Laminates and Coated Products Engineered  
to Solve EMI/RFI Shielding Problems

PRODUCT: A-16-NPS

CONSTRUCTION: .001" Aluminum Foil  
.0005" Polyester Film

APPLICATION: E.M.I. and R.F.I. shielding of electronic components

SPECIFICATION: FCC Part is sub-part J. Vol. II, July 1981

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness	.0015"	ASTM-D-374
Peel Strength	Not Applicable	
Tensile Strength	10,000 P.S.I.	ASTM-D-882
Elongation at Break	25 %	ASTM-D-882
Color	Silver	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 424

date 06/23/97

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.  
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible  
Laminated and Coated Products.  
Fabrics.

•Electrical and Electronic Shielding  
and insulation Composites.

•Specialty Pressure Sensitive Tapes-  
Laminates-Films, Foils, Papers,