



# LAMART CORPORATION

Flexible Laminate Solutions

## Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: 10181-L Tape

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**  
Products Engineered to your Specifications

CONSTRUCTION: 0.00035 aluminum foil  
0.00048" polyester film  
0.0025" acrylic pressure sensitive adhesive  
90# tight release liner

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.0038" +/- 10%	ASTM-D-365I-83
Peel Strength:	45 oz./inch of width	ASTM-D-1000
Tensile Strength:	6,000 P.S.I.	ASTM-D-882
Elongation at Break:	90%	ASTM-D-882
Color:	Silver	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 10181

Rev 2: 02/21/07

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.*

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics