



# LAMART CORPORATION

Flexible Laminate Solutions

## Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT: A 25 50dk 7665

DESCRIPTION: **CUSTOM PRODUCTS**  
Laminates and Coated Products  
Engineered for Industry

CONSTRUCTION: 0.00035 Alum Foil / 0.002 PET with a 50# densified kraft  
Liner and a rubber based PSA

FEATURES: Product offers good adhesion to polyethylene foam and other  
Low energy surfaces

ADHESIVE: Rubber based pressure-sensitive

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	.0032" +/- 10% without liner	ASTM-D-3652
Opacity:	Opaque	
Dimensional Stability:	Excellent	
Adhesion to stainless steel:	> 50 oz/inch of width @ 75 degrees F	ASTM-D-1000
Adhesion to polypropylene:	> 50 oz/inch of width @ 75 degrees F	15 minute dwell
Min. Application Temperature:	50 degrees F	
Service Temperature:	Not established	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 10897

Date 03/07/03

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.*

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics