



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT: PFP 575 Red 50DK/P

DESCRIPTION: **CUSTOM PRESSURE SENSITIVE PRODUCTS**

MATERIAL: 0.0006" Polypropylene
0.0007" Aluminum Foil
0.0006" Polypropylene
Acrylic pressure sensitive adhesive
Liner - 50 # densified kraft release liner

PROPERTY	VALUE		TEST METHOD
	MIN.	MAX.	
Material Thickness polypropylene/foil/ polypropylene without adh.	0.0017"	0.0025"	ASTM-D-374
Release value from liner GMS/Inch of Width	4 gms.	50 gms.	* LTM # 18
Pressure Sensitive Adhesive Thickness	0.0011"	0.0014"	ASTM-D-3652
Peel Strength Oz/Inch of Width	> 32 oz.	1hr dwell	PSTC # 1
Color:	Red		
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% RH.		

* LTM: Lamart Test Method

PN 1124

Rev 1: 02/02/05

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics