



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: GOLD RACING TAPE

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**
Products Engineered to your Specifications

CONSTRUCTION: Metallized polyimide film
laminated to glass cloth
with high temp acrylic adhesive
protected by a release liner

FEATURES: Excellent heat reflective
characteristics. Easy to install.
Withstands 675F of radiant heat for a minimum of 8 hours.

APPLICATION: Heat reflective material used
in the auto racing industry.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness w/o liner	.0065" +/- 10%	ASTM-D-3652
Adhesion off stainless steel:	32 oz/inch of width minimum	ASTM-D-1000
Weight w/o liner:	5.04 oz / sq yd	LTM 25A
UV Stability of Adh:	Excellent	
Color:	Gold	
Shelf Life;	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	
Adhesive residue removal	Any adhesive residue remaining after removal of Gold Racing Tape can be dissolved using MEK, Toluene or gasoline.	

P/N 11417

Rev1: 12/29/04

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics