



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: 213-M-L TAPE

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**
Products Engineered to your Specifications

CONSTRUCTION: Backing: 0.003" Soft Aluminum
Adhesive: 0.002" Acrylic Pressure Sensitive Adhesive
Liner : Poly coated Kraft

APPLICATION: Paint stripping, mask-off tape where
exceptional resistance to paint stripping
solvents, jet fuel, etc. is required.

SPECIFICATION: MIL-T-23397b, MIL-T-23397c

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.005 inch +/- 10%	ASTM-D-3652
Peel Strength:	50 oz./inch of width	ASTM-D-1000
Breaking Strength:	26 lbs./inch of width	ASTM-D-1000
Elongation at Break:	5%	ASTM-D-1000
Color:	Silver	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 1203

Date: 05/21/07

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics