



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: WAXGRIP

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**
Products Engineered to your Specifications

CONSTRUCTION: Clear LDPE
Acrylic pressure sensitive adhesive

APPLICATION: Tape is used to cover glass and plastic lenses during processing to protect the lenses. Offers clean removal after extended periods of time. Handles easily using either manual or automatic application methods.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
:	0.0028 inch +/- 10%	ASTM-D-3652
Peel Strength:	16 oz./inch of width	ASTM-D-1000
Color:	Clear	
Tensile:	8.0 lbs/inch	
Elongation:	325%	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 12748

Date 04/28/06

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics