



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID:	604 TAPE
DESCRIPTION:	PRESSURE SENSITIVE PRODUCTS Products Engineered to your Specifications
CONSTRUCTION:	Backing: 0.001" gold metallized polyester Adhesive: 0.001" acrylic pressure sensitive Interliner: Available
FEATURES / BENEFITS:	Extensible film is useful when tape has to form a curve. Highly reflective gold metallization makes this tape perfect for decorative applications. Aggressive acrylic PS adhesive is designed to offer excellent quick stick and ultimate adhesion.
APPLICATION:	Decorative striping for boats, toys, or appliances. Edging tape for charts, albums, or covers. It can be supplied on an interliner.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.002 inch +/- 10%	ASTM-D-3652
Peel Strength:	32 oz./inch of width	ASTM-D-1000
Breaking Strength:	18 lbs./inch of width	ASTM-D-1000
Elongation at Break:	100%	ASTM-D-1000
Color:	Gold	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 489

Rev. 1: 04/26/07

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics