



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: ALLOYGRIP 1

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**
Products Engineered to your Specifications

CONSTRUCTION: 0.0035" polyethylene
53PS Release liner

APPLICATION: Protects lenses during the lens generation process.

BENEFITS: -Lens scratching is eliminated. The alignment marks are protected from the generating solution because of superior bond between the lens tape and the lens – even on high index lenses.
-The attachment medium forms an excellent bond to the tape, preventing premature release during lens generation in both wet and dry processes. Deblocking is quick, and the tape removes residue free from the lens, leaving alignment marks in place.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.0044 inch +/- 10%	ASTM-D-3652
Peel Strength:	26 oz. piw off plastic 24 oz piw off glass	ASTM-D-1000
Color:	Blue	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	
P/N 6742		Date: (Rev.2) 09/09/08

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics