



# LAMART CORPORATION

Flexible Laminate Solutions

## Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: LF-200-H-TC-90-U97

DESCRIPTION: **GRAPHIC ARTS**  
Laminates and Coated Products Engineered for the Graphic Arts Industry

CONSTRUCTION: 0.0016" hard commercially bright aluminum foil  
Top-coated, acrylic PSA, 90# liner

APPLICATION: Appliance labels, dials, or control panels. Product nameplates and instruction panels. Tamperproof labels.

ADHESIVE: Permanent acrylic pressure sensitive, UL approved:  
Marking & Labeling System Materials

CHEMICAL PROPERTIES: Resistant to mild acids, alkalies, and salt.  
Fungus resistant. Water and corrosion resistant.

PRINTING METHODS: Letterpress, Offset, Screen, Flexo

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness (Foil + Adhesive):	0.0026 in +/- 10%	ASTM-D-3652
Durability:	3 years	
Adhesion:	> 32oz.	ASTM-D-1000 15-min. dwell
Service Temperature:	-40 to 250 degrees F.	
Application Temperature:	50 degrees F.	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 9218

Date 05/14/02

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.*

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics